

## COLOR GELS

Page 1 of 7

MSDS#: KIG112900-CLG

Section 1 – Identification

**COLOR GELS Product Name:** 

Manufacturer: ABC International Sp. z o.o.

Ul. Odolańska 10 Warszawa 02-560

**Emergency Phone Numbers:** (0048)42 631 47 24

Family: UV GELS **Product Use: NAIL GEL Product #: various** 

**Chemical Name:** 

**Information Contacts:** (0048)228800455

### Section 2 - Hazards Identification

### **EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.

May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

N/A

May cause chemical burn in eye.

### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact

may cause slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening

and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since

irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that may be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be

irritating.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A

lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

### Section 3 - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH	Carcinogen	%
				TWA/STEL	TWA/STEL	IARC/NTP/OSHA	
Polyurethane Acrylate Oligomer	72869-86-84	276-957-5	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	70-80
Ethylene glycol dimethacrylate	97-90-5	202-617-2	Glycol HEMA- Methacrylate	N/E	N/E	Not Listed	20-30
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	3-5
Benzophenone	119-61-9	204-337-6	Benzophenone	N/E	N/E	Not Listed	3-5
May Contain the follo	wing:						
Please see Section 16 for N/E - None Established N/R - Not Reviewed	or additional compound N/DA - No Data Available N/A - Not Applicable		* See section 16				

Polyurethane Acrylate Oligomer: Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S3/7, S36/37, S62 Ethylene Glycol Dimethacrylate: Hazard Symbol: Xi Risk Phrases: R37, R43 Safety Phrases: S2, S24, S37 Hydroxycyclohexyl Phenyl Ketone: Hazard Symbol: Xi Risk Phrases: R36, R37, R38 Safety Phrases: S26, S37

Benzophenone: Hazard Symbol: Xi Risk Phrases: R36, R38 Safety Phrases: S26

See Section 16 for Risk and Safety Phrase Key

#### Section 4 - First Aid Measures

First Aid for Eye Flush with plenty of water for 15 minutes and seek medical attention.



## COLOR GELS

Page 2 of 7

MSDS#: KIG112900-CLG

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

#### Section 5 - Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
> 212°F/100°C Setaflash	No Data	No Data

Method:

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Instructions: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective

equipment when entering confined areas where potential for exposure to vapors or products of combustion

exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in

explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control

fires since frothing can occur.

#### Section 6 - Accidental Release Measures

Spill or Release Procedures Spontaneous polymerization can occur. Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

### Section 7 - Handling and Storage

Handling Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure

to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods ( including shoes ). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after

handling. Solvents should not be used to clean skin because of increased penetration potential.

Storage Store in a cool place, away from heat and light. Store at temperatures below 100° F.

Explosion Hazard High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and

the violent rupture of storage vessels or containers.

#### Section 8 - Exposure Controls / Personal Protection

Engineering Controls Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations

generating vapors.

### **Personal Protective Equipment**

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole

body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Wear chemical splash goggles.
Skin Protection Wear impervious gloves (Neoprene).

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN

149.



## **COLOR GELS**

Page 3 of 7

MSDS#: KIG112900-CLG

### Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	PH	Specific Gravity	Viscosity	% Volatile
White, mobile liquid	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume : < 0.5

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20°C:< 0.01	No Data	No Data	No Data	Insoluble

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
> 212°F/100°C Setaflash	No Data	No Data

### Section 10 - Stability and Reactivity

Stability Incompatibility (Materials to Avoid):

Normally Stable Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

Hazardous Decomposition Products: Hazardous Polymerization:

Fumes produced when heated to decomposition may include:

carbon monoxide, carbon dioxide.

May occur -- Uncontrolled polymerization may cause rapid evolution of Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

**Conditions to Avoid:** 

Storage > 100° F, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

### Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No information available	No information available	No information available	No information available	No information available
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the				

oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

#### Section 12 - Ecological Information

**Ecotoxicological Information** 

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

#### **Chemical Fate Information**

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil

#### Section 13 - Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the genrators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

#### Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	N/A
Emergency Response Guidebook (ERG) #:	N/A



MSDS#: KIG112900-CLG

# **Material Safety Data Sheet**

# **COLOR GELS**

Page 4 of 7

IATA (DGR):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	
Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	
Other Information:	Flash point > 100°C

## Section 15 - Regulatory Information

## **US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP and ODS's), as defined by the U.S. Clean Air Act:    Benzophenone, CAS# 119-61-9 (SOCMI)
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are:  ☐ Immediate (acute) health hazard ☐ Delayed (chronic) health hazard ☐ Reactive hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261):    Ethyl Acetate, CAS# 141-78-6: RCRA Code: U112
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 302 as extremely hazardous chemicals for emergency release notification ("CERCLA" List):  Ethyl Acetate CAS# 141-78-6, RQ (5000lbs.)  Butyl Acetate CAS# 123-86-4, RQ (5000lbs.)
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are:    Immediate (acute) health hazard   Delayed (chronic) health hazard   Reactive hazard
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory: TSCA Significant New Use Rule:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.  None of the chemicals listed have a SNUR under TSCA.
1551 biginificant flow obc Rule.	11010 of the chemicals inseed have a Sixor under 15011.

### **State Regulations**

CA Right-to-Know Law:	Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS# 123-86-4
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS# 123-86-4
NJ Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS# 123-86-4
PA Right-to-Know Law:	Titanium Dioxide CAS #13463-67-7, Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS#



## **COLOR GELS**

Page 5 of 7

MSDS#: KIG112900-CLG

	123-86-4
FL Right-to-Know	Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS# 123-86-4
MN Right-to-Know	Benzophenone, CAS #119-61-9, Titanium Dioxide CAS #13463-67-7, Ethyl Acetate CAS# 141-78-6, Butyl Acetate CAS# 123-86-4

**International Regulations** 

CDSL: Canadian Inventory	Titanium dioxide CAS # 13463-67-7 is on the DSL list. WHMIS = n/da
(on Canadian Transitional List)	Hydroxycyclohexyl phenyl ketone CAS #947-19-3 is on the DSL list. WHMIS = n/da
	Benzophenone, CAS #119-61-9 is on the DSL list. WHMIS = n/da
	Ethylene glycol dimethacrylate CAS #97-90-5 is on the DSL list. WHMIS = D2B.
	Ethyl Acetate CAS #141-78-6 is on the DSL list. WHMIS = B2, D2B
	Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B

Labeling according to EC directives – 1999/45/EC

European Community:	Color Gels:
	☐ HAZARD SYMBOLS: <b>Xi:</b> Irritant
	☐ RISK PHRASES: <b>R22:</b> Harmful if swallowed, <b>R36/38:</b> Irritating to eyes and skin,
	R43: May cause sensitization by skin contact.
	□ SAFETY PHRASES: <b>S18:</b> Handle and open container with care, <b>S24/25:</b> avoid
	contact with skin and eyes, \$36/37: Wear suitable protective clothing and gloves,
	S38: in case of insufficient ventilation, wear suitable respiratory equipment.

### Section 16 - Other Information

#### EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

#### **Hazard Symbol:**

Xi - Irritants


#### **Risk Phrases:**

R36/37/38 Irritating to eyes, respiratory system and skin

#### Safety Phrases:

S2 Keep out of the reach of children; S3/7 Keep container tightly closed in a cool place; S24 Avoid contact with skin; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S36/37 Wear suitable protective clothing and gloves; S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

Hazard Rating System (Pictograms)



MSDS Prepared by:	BSQ
Revision History:	11/29/2000 Initial Issue.
	09/21/2004 Overall format update and changes to section 2 & 16 % contents.
	11/08/2004 Overall format update and changes to section 2 & 16 % contents.
	01/10/2006 Update spelling in section 16.
	08/02/2007 Section one 1 format update.



## **COLOR GELS**

Page 6 of 7

MSDS#: KIG112900-CLG

03/14/2008 Updated section 16
04/30/2008 Updated INCI name for Polyurethane Acrylate Oligomer.  * Most ABC gels are composed of oligomers made primarily from urethane methacrylates. ABC is using the designation Di HEMA Trimethylhexyl Dicarbamate, the official INCI name of urethane dimethacyrlate, which is substantially the equivalent of Polyurethane Acrylate Oligomer.
09/16/2008 Updated section 16
10/03/2008 Updated pigments in "May Contain" list
10/22/2008 Updated format
11/10/2008 Updated Risk and Safety Phrases
03/03/2009 Added Bismuth Oxychloride to "may contain"
03/09/2009 Updated EINECS number of Blue#1 in section 16
03/18/2009 Updated to meet Globally Harmonized System requirements. Added
the EU address to section 1. Switched location of section 2 with section 3.
Changed the title in sections 1, 8, and 13. Moved MSDS preparation to section
16.
03/27/2009 Updated the EC# for Red 34, Red 6, Yellow 5, and Mica. Removed
Burnt umber from the May contains.

MAY CONTAIN THE Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
Chemical Identity	CAS Numbers	EINECSπ	INCI Name	OSHA TWA/STEL	ACGIH TWA/STEL	IARC/NTP/OS HA	70
Titanium Dioxide	13463-67-7	236-675-5	Titanium Dioxide/CI77891	15 mg/m3	10 mg/m3	3/no/no	0-1
Manganese Violet	10101-66-3	233-257-4	Manganese Violet/CI77742	N/E	N/E	Not Listed	0-1
FD&C Blue #1	3844-45-9	223-339-8	Blue 1/CI42090	N/E	N/E	Not Listed	0-1
FD&C Yellow #5	1934-21-0	217-699-5	Yellow 5/CI19140	ND/A	ND/A	Not Listed	0-1
Yellow Iron Oxide	51274-00-1	N/E	Iron oxides/CI77492	N/E	N/E	Not Listed	0-1
Raw Umber	1309-37-1	215-168-2	Iron oxides/CI77491	N/E*	N/E*	Not Listed	0-1
Red Iron Oxide	1332-37-2	215-570-8	Iron Oxide/CI77491	N/E*	N/E*	Not Listed	0-1
D&C Red #34	6417-83-0	229-142-3	Red 34/CI15880	N/E	N/E	Not Listed	0-1
D&C Red #7	5281-04-9	226-109-5	Red 7/CI15850	N/E	N/E	Not Listed	0-1
D&C Red #6	5858-81-1	227-497-9	Red 6/CI15850	N/E*	N/E*	Not Listed	0-1
Synthetic Red Iron Oxide	1309-37-1	N/E	Iron Oxides/CI77491	N/E	N/E	Not Listed	0-1
(maroon)							
D&C Orange No.4	633-96-5	211-199-0	Orange 4/CI15510	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	Violet 2/CI60725	N/E	N/E	Not Listed	0-1
Mica	12001-26-2	310-127-6	Mica	N/E	3 mg/m	Not listed	0-1
Ferric Ammonium Ferrocyanide	25869-00-5	247-304-1	Ferric Ammonium Ferrocyanide /CI77510	N/E	N/E	Not Listed	0-1
D&C Yellow #10	8004-92-0	305-897-7	Yellow 10/CI47005/ E104	N/DA	N/DA	N/DA	0-1
Ultramarine Blue	57455-37-5	N/DA	Ultramarines/CI77007	N/DA	N/DA	N/DA	0-1
Iron Oxide Black	1317-61-9	215-277-5	Iron Oxide/CI77499	N/E*	N/E*	Not Listed	0-1
Carbon Black	1333-86-4	215-609-9	Carbon Black/CI77266	3.5 mg/m <sup>3</sup>	0.1 mg PAH's/m <sup>3</sup> carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)	Group 2B / A-4 / Possible Select Carcinogen	0-1
Bismuth Oxychloride	7787-59-9	232-122-7 (I)	Bismuth Oxychloride/CI77163	N/E	N/E	Not Listed	0-1
N/E - None Established N/R - Not Reviewed	N/DA–No Data Ava N/A-Not Applicable						

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (0048)42 631 47 24.



**COLOR GELS** 

Page 7 of 7

MSDS#: KIG112900-CLG

KRP components are provided on an as is basis without warranties of any kind either expressed or implied. KRP does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said KRP components.